Revision Date: 2013/04/05

Section 1: PRODUCT INFORMATION

Chemical family: Mixture.Product uses: Varnish.Product name: 10VOC

Manufacturer: Flame Control Coatings Inc.

4120 Hyde Park Blvd.,

P.O.Box 786

Niagara Falls, New York, 14305.

Manufacturer emergency phone

number:

800-535-5053

Supplier: Same as manufacturer.

TDG classification:

PAINT UN1263 Class 3 PG III.

WHMIS classification:

B3, D2A, D2B.





DSL status: The substance(s) which appear in section 2 with CAS numbers appear on the

Domestic Substances List.

Supplier MSDS date: 2013/04/04.

Section 2: HAZARDOUS INGREDIENTS

C.A.S.	CONCENTRATION %	Ingrédient	V.L.E.	DL/50	CL/50
108-67-8	1–5	1,3,5-TRIMETHYLBENZENE	25 PPM	7000 MG/KG MOUSE ORAL	24,000 MG/M3/4H RAT INHALATION
				5000 MG/KG RAT ORAL	
1330–20–7	0.1–1.0	XYLENE	100 PPM	4300 MG/KG RAT ORAL 2119 MG/KG MOUSE ORAL >1700 MG/KG RABBIT DERMAL	5000 PPM/4 HR RAT INHALATION
25340-17-4	1–5	DIETHYLEBENZENE	NOT AVAILABLE	3000 MG/KG RABBIT ORAL	NOT AVAILABLE
64742-95-6	40-70	LIGHT AROMATIC SOLVENT NAPHTHA (C8-C10)	NOT AVAILABLE	8400 MG/KG RAT ORAL	NOT AVAILABLE
95-63-6	10–30	1,2,4 TRIMETHYL BENZENE	25 PPM	5000 MG/KG RAT ORAL 6900 MG/KG MOUSE ORAL	18,000 MG/M3/4H RAT INHALATION
98-82-8	1–5	CUMENE	50 PPM	1400 MG/KG RAT ORAL 12750 MG/KG MOUSE ORAL 12300 UL/KG RABBIT DERMAL	10,000 MG/M3/7 HRS MOUSE INHALATION 39,000 MG/M3/4H RAT INHALATION

10VOC – 10VOC 1/6

Section 2A: ADDITIONAL INGREDIENT INFORMATION

Note: (supplier).

CAS# 64742-95-6 TLV 400 ppm.

Section 3: PHYSICAL DATA

Physical state: Liquid.

Appearance & odor: Clear

Aromatic solvent odour.

Odor threshold (ppm): Not available.

Vapour pressure (mmHg): (solvent).

2.1

Vapour density (air=1): 4.5

Volatiles (%)

By volume: 73%

Evaporation rate Not available. (butyl acetate = 1):

Boiling point ($^{\circ}$ C): (solvent).

Freezing point (°C): Not available.

pH: Not applicable.

Specific gravity @ 20 °C: 1.0-1.1.

Solubility in water (%): Insoluble.

Coefficient of water\oil dist.: Not available.

VOC: (material). 638 g/l.

Section 4: FIRE & EXPLOSION DATA

Flammability: Combustible.

Conditions of flammability: Vapours are heavier than air and may travel along the ground and be ignited by

flames, sparks or other ignition sources at locations distant from the material

handling point.

Heat, sparks and open flames. Vapours may cause flash fire.

Extinguishing media: Dry chemical.

Alcohol foam. Water fog. Carbon dioxide.

Special procedures: Self-contained breathing apparatus required.

Firefighters should wear the usual protective gear. Use water spray to cool fire exposed containers.

Auto-ignition temperature (°C): 488

10VOC - 10VOC 2/6 **Flash point** (°C), **method:** Tag Closed Cup.

42°C.

Lower flammability 0.9

limit (% vol): U.

Upper flammability

limit (% vol): 6.09

Explosion Data

Sensitivity to static discharge: Take precautionary measures against static discharge.

Sensitivity to mechanical impact: Not available.

Hazardous combustion products: Oxides of carbon (CO, CO2).

Acids Aldehydes.

Toxic and irritating vapours.

Explosive power: May form explosive peroxides.

Contact with oxidizers may cause fire or explosion.

Section 5: REACTIVITY DATA

Chemical stability: Stable under normal conditions.

Conditions of instability: None known.

Hazardous polymerization: Will not occur.

Incompatible substances: Strong acids.

Oxidizing agents. Perchlorates. Nitrates. Peroxides.

Reactive materials. Hypochlorites.

Phosphorous compounds.

Hazardous decomposition Carbon monoxide.

products: Carbon dioxide.

Section 6: TOXICOLOGICAL PROPERTIES

Route of entry: Eye contact, skin contact, skin absorption, inhalation and ingestion.

Effects of acute exposure

Eye contact: May cause pain.

Severe irritant.

May cause redness and tearing.

May cause swelling. May cause itching.

May cause irreversible corneal damage.

Skin contact: May cause dermatitis.

Irritant.

May cause defatting.

May cause drying and cracking.

10VOC – 10VOC 3/6

Skin absorption: May be harmful if absorbed through the skin.

See inhalation effects.

Inhalation: Harmful if inhaled.

Irritation of the respiratory tract.

May cause narcosis. May cause loss of appetite.

Vapors may irritate nose, throat and eyes. May cause headache, dizziness and nausea.

May cause fatigue.

May cause tightness of the chest.

Ingestion: May cause digestive tract irritation.

May cause nausea, vomiting and diarrhea.

May cause sore throat.

Aspiration of material into lungs may cause chemical pneumonitis.

May cause abdominal pain. Harmful or fatal if swallowed.

Effects of chronic exposure: May cause conjunctivitis.

May cause liver and kidney damage.

May cause corneal damage.

Prolonged occupational overexposure to solvents may lead to permanent brain and

nervous system damage. May cause blood damage. May cause skin and eye damage.

May cause damage to the gastrointestinal tract. Allergies may be aggravated by this product. May cause damage to upper respiratory tract. May cause damage to the central nervous system.

Pre-existing skin conditions may make the skin more susceptible to the effects of

this product.

May cause loss of coordination and mental confusion.

LD50 of product, species & route: 5600 mg/kg rat oral.

> 4000 mg/kg rabbit dermal.

LC50 of product, species & route: Not available for mixture, see the ingredients section.

Exposure limit of material: Not available for mixture, see the ingredients section.

Sensitization to product: Yes

Carcinogenic effects: Possible.

Reproductive effects: May cause adverse reproductive effects.

Teratogenicity: May cause teratogenic effects.

Mutagenicity: No **Synergistic materials:** No

Section 7: PREVENTATIVE MEASURES

Precautionary Measures

10VOC – 10VOC 4/6

Gloves/Type:



Nitrile rubber gloves.

Respiratory/Type: Not necessary, if adequate ventilation provided.

NIOSH approved respirator with organic vapor cartridge is required if ventilation is

inadequate or exposure limits are exceeded.

Eye/Type:



Splash proof chemical goggles. Chemical safety glasses.

Footwear/Type: Safety shoes per local regulations.

Clothing/Type: Long sleeve shirt, long trousers.

Other/Type: Eye wash facility should be in close proximity.

Emergency shower should be in close proximity.

Ventilation requirements: Exhaust ventilation.

To maintain exposure below TLV.

Leak/Spill: Eliminate all sources of ignition.

Soak up with an absorbent material.

Prevent entry into drains, sewers, and other waterways.

Ventilate area.

Wear appropriate protective equipment.

Use non-sparking tools.

Store in closed metal containers until disposal.

Waste disposal: Dispose in accordance with local, provincial/state, and federal regulations.

Incineration is the preferred method.

Handling procedures and Keep away from heat, sparks, and open flame.

equipment: Avoid breathing vapors/mists.

Use adequate ventilation. Wash thoroughly after handling.

Empty containers containing residue may cause a hazard.

Use proper grounding procedures.

Avoid contact with skin, eyes and clothing. Bond and ground during transfer of liquid. Launder contaminated clothing prior to reuse.

Storage requirements: Store away from incompatible materials.

Keep out of direct sunlight.

Keep away from heat, combustibles and reactive chemicals.

Keep containers tightly closed.

Store indoors.

Store in a cool, dry and well ventilated area.

Store in metal containers.

Store in a sprinklered warehouse.

10VOC – 10VOC 5/6

TDG classification:

PAINT UN1263 Class 3 PG III.



Special shipping information: See transportation information.

Section 8: FIRST AID MEASURES

Skin contact: Remove contaminated clothing.

Flush with large amounts of water, for at least 15 minutes.

Seek medical attention if irritation persists.

Eye contact: Immediately flush eyes with running water for a minimum of 15 minutes. Hold

eyelids open during flushing. Obtain medical attention immediately.

Inhalation: Remove victim to fresh air. If breathing is difficult administer oxygen. If not

breathing, have qualified person give artificial respiration. Obtain medical attention.

Ingestion: Do not induce vomiting, seek medical attention.

Never give anything by mouth to an unconscious person.

If conscious, give 3–4 glasses of water or milk.

Additional information: The above information is believed to be correct but does not purport to be all

inclusive and shall be used only as a guide. This company shall not be held liable

for any inaccuracies.

Note to physician: Treat symptomatically.

Section 9: ADDITIONAL INFORMATION

General note: This material safety data sheet was prepared from information obtained from

various sources, including product suppliers and the Canadian Center for

Occupational Health and Safety.

This MSDS was generated by Conform-Plus Application Service. Visit us at www.netmsds.com.

10VOC – 10VOC 6/6